



Hardfloor ISO 2K Hardener

Isocyanite 2K Hardener for PU Coating

Hardfloor ISO 2K hardener is a very effective hardener that activates and strengthens Hardfloor PU-Coating

- Ensures optimal curing and final result
- Improves drying time and effective evaporation
- Supports maximum wear resistance and durability

Application area

Work description

Preparation

It is important that the surface and PU-Coating have a temperature of at least 15 °C (ideally around 20 °C), and that the humidity is around 50%. At the same time, ensure good ventilation in the room to ensure optimal evaporation and correct drying time.

Please note

When the hardener and PU coating are mixed, the open time is a maximum of 4 hours. See the technical data sheet for Hardfloor PU coating regarding drying times and correct application.

Technical data

Shelf life: 3 years

Colours: Colourless

Storage: +10-30°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging sizes: 500 ml

Mixing ratio: 500 ml for 4.5 L PU Coating

Maintenance and related products

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.